



AIR LIQUIDE AMERICA SPECIALTY GASES LLC
Air_Liquide_America_Specialty_Gases,_LLC

MATERIAL SAFETY DATA SHEETS

DATE: 4/30/08

SUPPLIER ADDRESS: 500 WEAVER PARK RD

LONGMONT, CO 80501
EMERGENCY PHONE: (888) 253-1635
NUMBER

1. CHEMICAL PRODUCT

PRODUCT NAME: PROPANE

SYNONYMS: Dimethylmethane

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient Name	Formula	CAS#	Concentration	Exposure Limits (PPM)			
				ACGIH TLV	OSHA PEL	MAC	Other STEL
PROPANE	C3H8	74-98-6	99+%	2500	1000	NE	NE

Note: NE = NONE ESTABLISHED

3. HAZARD IDENTIFICATION

*** EMERGENCY OVERVIEW ***

Flammable liquid and gas under pressure.
Can form explosive mixtures with air.
May cause frostbite.

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation , Skin

ACUTE EFFECTS: Material acts as a simple asphyxiant by displacing air necessary for life. Symptoms include rapid respiration, muscular incoordination, fatigue, dizziness, nausea, vomiting, unconsciousness, and death. Pressure drop through valves and piping may cause extreme cold and frostbite on contact.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: None known

OTHER EFFECTS OF OVEREXPOSURE: None

CARCINOGENICITY (US Only):

NTP - No
IARC MONOGRAPHS - No
OSHA REGULATED - No

Continued ...



4. FIRST AID MEASURES

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

EYE CONTACT: None

SKIN CONTACT: If frostbite occurs, flush affected areas with lukewarm water.

INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: For frostbite, consider rapid rewarming at 42 deg.C. Do not institute rewarming unless complete rewarming can be assured.

5. FIRE FIGHTING MEASURES

FLASH POINT: -105 deg.C

AUTOIGNITION TEMPERATURE: 450 deg.C

FLAMMABLE LIMITS: Vol.%

LOWER: 2.1

UPPER: 9.5

EXTINGUISHING MEDIA: Carbon dioxide, water spray, or dry chemical.

SPECIAL FIRE FIGHTING INSTRUCTION AND EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing. Keep fire exposed cylinders cool with water spray. If possible, stop the product flow.

HAZARDOUS COMBUSTION PRODUCTS: Toxic carbon monoxide may be given off during combustion.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Severe when exposed to heat or flame. Vapors may travel a considerable distance to the source of ignition and flash back. May form explosive mixture in air. Cylinder rupture may occur under fire conditions.

6. ACCIDENTAL RELEASE MEASURES

CLEAN UP PROCEDURES: Evacuate and ventilate area. Remove leaking cylinder to exhaust hood or safe outdoor area. Shut off source if possible and remove source of heat.

SPECIALIZED EQUIPMENT: None

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store in well ventilated areas. Keep valve protection cap on cylinders when not in use.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain concentrations below exposure and flammable limits.

PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses

SKIN PROTECTION: Protective gloves to prevent contact with cold equipment.

RESPIRATORY PROTECTION: In case of leakage, use self-contained breathing apparatus.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless

ODOR: Sweet odor.

PHYSICAL STATE: Liquefied gas.

VAPOR PRESSURE: @21.1 deg.C: 8.42 atm

VAPOR DENSITY (AIR=1): 1.55

BOILING POINT (C): -42.1

SOLUBILITY IN WATER: @18 deg.C v/v:
0.065

SPECIFIC GRAVITY (H2O=1): @20 deg.C:
0.501

Continued ...



EVAPORATION RATE: Gas

ODOR THRESHOLD: 5,000 to 20,000 ppm

10._STABILITY_AND_REACTIVITY_____

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Storage near a heat source.

MATERIALS TO AVOID: Oxidizing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: Carbon oxides form when burned.

11._TOXICOLOGICAL_INFORMATION_____

LETHAL CONCENTRATION (LC50): None established

LETHAL DOSE 50 (LD50): N/Ap

TERATOGENICITY: N/Ap

REPRODUCTIVE EFFECTS: N/Ap

MUTAGENICITY: N/Ap

12._ECOLOGICAL_INFORMATION_____

No adverse ecological effects are expected.

13._DISPOSAL_CONSIDERATIONS_____

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. If the cylinders are the refillable type, return cylinders to supplier with any valve outlet plugs or caps secured and valve protection caps in place.

14._TRANSPORT_INFORMATION_____

CONCENTRATION: 99+%

DOT DESCRIPTION (US ONLY):

PROPER SHIPPING NAME: Propane

HAZARD CLASS: 2.1 (flammable)

IDENTIFICATION NUMBER: UN1978

REPORTABLE QUANTITIES: None

LABELING: FLAMMABLE GAS

ADR/RID (EU Only): Class 2, 2f

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well ventilated truck.

15._REGULATORY_INFORMATION_____

OSHA: Process Safety Management: Material is not listed in appendix A of 29 CFR 1910.119 as highly hazardous chemical.

TSCA: Material is listed in TSCA inventory.

SARA: The threshold planning quantity for material is 10,000 lbs.

EU NUMBER: 200-827-9

NUMBER IN ANNEX 1 OF DIR 67/548: Not listed in annex 1.

EU CLASSIFICATION: N/Av

R: 13

S: 9-16-33

16._OTHER_INFORMATION_____

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

ABBREVIATIONS:

N/Ap - Not Applicable

N/Av - Not Available

SA - Simple Asphyxiant

NE - None Established

DISCLAIMER: Information included in this document is given to the best of our knowledge, however, no warranty is made that the information is accurate or complete. We do not accept any responsibility for damages by the use of the document.