



AIR LIQUIDE AMERICA SPECIALTY GASES, LLC  
Air\_Liquide\_America\_Specialty\_Gases,\_LLC

MATERIAL SAFETY DATA SHEETS  
DATE: 10/31/07

SUPPLIER ADDRESS: 500 WEAVER PARK RD  
  
LONGMONT, CO 80501  
EMERGENCY PHONE: (888) 253-1635  
NUMBER

## 1. CHEMICAL PRODUCT

PRODUCT NAME: METHANE

SYNONYMS: None

## 2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient Name	Formula	CAS#	Concentration	Exposure Limits (PPM)			
				ACGIH TLV	OSHA PEL	MAC	Other STEL
METHANE	CH <sub>4</sub>	74-82-8	99+%	S/A	S/A	S/A	S/A

Note: S/A = SIMPLE ASPHYXIAN

## 3. HAZARD IDENTIFICATION

\*\*\* EMERGENCY OVERVIEW \*\*\*  
Flammable high pressure gas.  
Can form explosive mixtures with air.  
Can cause rapid suffocation.

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation

ACUTE EFFECTS: Material acts as a simple asphyxiant by displacing air necessary for life. Symptoms include rapid respiration, muscular incoordination, fatigue, dizziness, nausea, vomiting, unconsciousness, and death.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: None known

OTHER EFFECTS OF OVEREXPOSURE: None

CARCINOGENICITY (US Only):

NTP - No  
IARC MONOGRAPHS - No  
OSHA REGULATED - No

Continued ...



---

## 4. FIRST AID MEASURES

---

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

EYE CONTACT: None

SKIN CONTACT: None

INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: None

---

## 5. FIRE FIGHTING MEASURES

---

FLASH POINT: -136.11 deg.C

AUTOIGNITION TEMPERATURE: 537 deg.C

FLAMMABLE LIMITS: In air at 1 atm.

LOWER: 5%

UPPER: 15%

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, or halocarbon gas.

SPECIAL FIRE FIGHTING INSTRUCTION AND EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing. Keep fire exposed cylinders cool with water spray. If possible, stop the product flow.

HAZARDOUS COMBUSTION PRODUCTS: Toxic carbon monoxide may be given off during combustion.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cylinder rupture may occur under fire conditions. May form explosive mixture in air.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

CLEAN UP PROCEDURES: Evacuate and ventilate area. Remove leaking cylinder to exhaust hood or safe outdoor area. Shut off source if possible and remove source of heat.

SPECIALIZED EQUIPMENT: Painting suspected area with soap solution may be

used to detect a leak.

---

## 7. HANDLING AND STORAGE

---

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders. No part of cylinder should be exposed to temperatures above 52 degrees celsius.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store in well ventilated areas. Keep valve protection cap on cylinders when not in use.

---

## 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

---

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain concentrations below flammable limits and to avoid asphyxiation.

### PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses

SKIN PROTECTION: None

RESPIRATORY PROTECTION: In case of leakage, use self-contained breathing apparatus.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE: Colorless

ODOR: Odorless

PHYSICAL STATE: Gas

VAPOR PRESSURE: N/Ap

VAPOR DENSITY (AIR=1): 0.55

BOILING POINT (C): -161

SOLUBILITY IN WATER: Slight

SPECIFIC GRAVITY (H2O=1): Gas

EVAPORATION RATE: Gas

ODOR THRESHOLD: N/Ap

---

## 10. STABILITY AND REACTIVITY

---

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Storage near a heat

Continued ...



source.

MATERIALS TO AVOID: Oxidizing agents.  
BrF<sub>5</sub>, Cl<sub>2</sub>, ClO<sub>2</sub>, NF<sub>3</sub>, liquid O<sub>2</sub>, and OF<sub>2</sub>.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: None

---

## 11.\_TOXICOLOGICAL\_INFORMATION

---

LETHAL CONCENTRATION (LC<sub>50</sub>): NONE  
ESTABLISHED

LETHAL DOSE 50 (LD<sub>50</sub>): N/Ap

TERATOGENICITY: N/Ap

REPRODUCTIVE EFFECTS: N/Ap

MUTAGENICITY: N/Ap

---

## 12.\_ECOLOGICAL\_INFORMATION

---

No adverse ecological effects are expected.

---

## 13.\_DISPOSAL\_CONSIDERATIONS

---

WASTE DISPOSAL METHOD: Non-returnable cylinders must not be refilled. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. Dispose of non-refillable cylinders in accordance with federal, state, and local regulations. Return cylinders to supplier with any valve outlet plugs or caps secured and valve protection cap in place.

---

## 14.\_TRANSPORT\_INFORMATION

---

CONCENTRATION: 99+%

DOT DESCRIPTION (US ONLY):

PROPER SHIPPING NAME: Methane,  
compressed

HAZARD CLASS: 2.1 (flammable)

IDENTIFICATION NUMBER: UN1971

REPORTABLE QUANTITIES: None

LABELING: FLAMMABLE GAS

ADR/RID (EU Only): Class 2, 1f

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well ventilated truck.

---

## 15.\_REGULATORY\_INFORMATION

---

OSHA: Process Safety Management:  
Material is not listed in appendix A of 29 CFR 1910.119 as highly hazardous chemical.

TSCA: Material is listed in TSCA inventory.

SARA: The threshold planning quantity for material is 10,000 lbs.

EU NUMBER: 200-812-7

NUMBER IN ANNEX 1 OF DIR 67/548:  
Material is listed in annex 1.

EU CLASSIFICATION: N/Av

R: 12

S: 9,16,33

---

## 16.\_OTHER\_INFORMATION

---

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

### ABBREVIATIONS:

N/Ap - Not Applicable

N/Av - Not Available

SA - Simple Asphyxiant

NE - None Established

DISCLAIMER: Information included in this document is given to the best of our knowledge, however, no warranty is made that the information is accurate or complete. We do not accept any responsibility for damages by the use of the document.